

Performance Nominals

High Back Pressure

Commercial Back Pressure

Model	HP	Displacement cc per Rev	Capacity						Cooling Type (CFM)	Oil Charge Qty (cc)	Net Wt. (Kg.)
			7.2°C			-6.7°C					
			Btu/Hr.	kCal/Hr.	Watt	Btu/Hr.	kCal/Hr.	Watt			
R22, 50 Hz, 1 Phase											
KCE443HAE	1/3	8.00	3600	907	1055	1620	408	475	Fan 350	510	11.8
KCE461HAE	2 1/2	11.50	5100	1285	1494	2590	653	759	Fan 350	510	13.4
KCJ511HAE	1	18.27	9150	2356	2740	4210	1061	1234	Fan 350	905	21.5
KCJ513HAE	1 1/4	25.91	12800	3226	3750	6366	1604	1865	Fan 350	890	22.5
CR22K6M-PF1	1 1/2+	40.80	19000	4788	5568	8920	2248	2614	Fan 400	1330	29.8
CR30K6M-PF1	2 1/2	51.47	25000	6300	7327	12000	3024	3516	Fan 400	1330	32.5
CR36K6-PFZ	3	59.65	30100	7585	8821	14200	3578	4161	Fan 400	1330	34.9
CR42K6-PFZ	3 1/2	72.09	36100	9097	10580	17300	4360	5069	Fan 400	1330	34.9
R22, 50 Hz, 3 Phase											
CR22K6M-TFM	1 1/2+	40.80	18350	4624	5377	8260	2082	2420	Fan 400	1330	29.5
CR30K6M-TFM	1/2	51.47	24400	6149	7149	11600	2923	3399	Fan 400	1330	30.0
CR36K6-TF6	3	59.65	29900	7535	8763	14500	3654	4249	Fan 400	1330	31.0
CR42K6-TF5	3 1/2	72.09	35100	7585	8821	17200	4334	5040	Fan 400	1330	32.7
KCG554HAE	4 1/2	99.96	45000	11340	13180	-	-	-	Fan 400	2250	50.1
KCG562HAE	5	117.66	52000	11057	15240	-	-	-	Fan 400	2250	50.7
KCG572HAE	6	133.22	60000	15120	17585	-	-	-	Fan 400	2250	51.4
R22, 60 Hz, 1 Phase											
KCJ511HAE	1	18.27	10500	2646	3077	4210	1061	1234	Fan 350	905	21.5