

[illegible]

2330/43KML-T17	95.3	[.722 - .768]
ZP51KUE-TFM	[.722 - .768]	

[illegible]

3.8
[8]



85
 [3.

96.5
 [3.8

15.4
 [4.54]

17.6
 [4.63]

DUE TO ACCUMULATED ASSEMBLY TOLERANCES
 THE LISTED COMPONENTS MAY VARY FROM

58.2

2 MOUNTING KIT.

E
233.3
SCALE 2:1

GROMMET DUROMETER
4 FOOT KIT

E

Ø 12.78-12.95 [0.503-0.510] I.D. ◆
 ▽10.10 [0.398] MIN.
 0.023-0.0255 MIN. THICK EXTERIOR

COMPRESSOR WIRING DIAGRAM


COPPER PLATED STEEL SECTION FITTING.

MINIMUM 75° C WIRE FOR AMPACITY.
DETERMINATION. INTERNAL MOTOR PROTECTION-
ALLOW TIME FOR RESET. PRIMARY SINGLE PHASE
FAILURE PROTECTION IS PROVIDED. CRANKCASE

[illegible][illegible]

ECN1026800	12	ADDED ZJ44KHE-TFM & ZP44KUE-TFM MODELS	03-14-16	C12	ZH	JOY
ECN102719	11	ADDED ZJ54KHE-TFM & ZP54KUE-TFM MODELS	03-09-16	SZ	ZH	JOY
ECN1027575	10	ADDED ZJ36KHE-TFM & ZP36KUE-TFM MODELS	02-25-16	A7	ZH	JOY

ECN101463	5	ADDED ZP54KUE-TF5 MODEL	06-15-15	CYZ	ZH	JOY
ECN101345	4	ADDED ZP44KUE-TF7 MODEL	04-17-15	NF	ZH	JOY



24 THIS DRAWING AND INFORMATION CONTAINED HEREIN ARE THE EXCLUSIVE PROPERTY OF EMERSON CLIMATE TECHNOLOGIES, INC. AND SHALL BE RETURNED TO THE ORIGINATOR.

CONFIDENTIALITY NOTICE

EMERSON CLIMATE TECHNOLOGIES, INC.

DESIGN STANDARDS DS2002

11/14/94 Y4 SV-1994

	TOLERANCES: 1- PLACE ± N/A 2- PLACE ± N/A ANGULAR ± N/A		TITLE REF DWG-WELD COMP ASSM	DRAWING NUMBER 497-1671-00	SHEET 1 OF 1 5 SIZE
---	--	---	---------------------------------	-------------------------------	---------------------------

12	11	10	9	8	7	6	5	4	3	UNCONTROLLED - DO NOT MODIFY
----	----	----	---	---	---	---	---	---	---	------------------------------