



Minimum Evaporating Temp. With:

- 20 °C Suction Gas Return ASERCOM certified Liquid injection
- 25 °C Suction Gas Return Liquid injection
- Maximum Evaporating Temperature

Suction Return Temperature 18.3°C

Liquid Subcooling 0.0K

Evaporating Temperature, °C

Cond °C	Cooling Capacity, kW										
	-40.0	-35.0	-30.0	-25.0	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0
10.0	4.48	5.66	7.06	8.74	10.75	13.10					
15.0	4.29	5.42	6.76	8.35	10.25	12.45	15.00				
20.0	4.09	5.17	6.45	7.95	9.72	11.80	14.20	17.05			
25.0	3.88	4.92	6.12	7.54	9.20	11.15	13.40	16.05	19.10		
30.0	3.64	4.64	5.79	7.12	8.67	10.50	12.60	15.10	17.95	21.20	22.60
35.0	3.39	4.34	5.43	6.68	8.13	9.83	11.80	14.10	16.75	19.80	21.10
40.0	3.10	4.02	5.05	6.22	7.57	9.15	11.00	13.10	15.55	18.40	19.65
45.0	2.78	3.67	4.65	5.74	6.99	8.45	10.15	12.10	14.35	17.00	18.15
50.0	2.43	3.29	4.21	5.23	6.39	7.72	9.27	11.05	13.15	15.60	16.65
55.0	2.04	2.87	3.74	4.69	5.75	6.97	8.38	10.00	11.95	14.15	15.15
60.0						6.19	7.46	8.94	10.65	12.70	13.60

Cond °C	Power, kW										
	-40.0	-35.0	-30.0	-25.0	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0
10.0	2.04	2.15	2.28	2.42	2.57	2.74					
15.0	2.16	2.27	2.40	2.55	2.71	2.88	3.07				
20.0	2.31	2.42	2.55	2.69	2.85	3.03	3.22	3.44			
25.0	2.51	2.62	2.74	2.87	3.03	3.21	3.40	3.61	3.84		
30.0	2.78	2.87	2.97	3.10	3.25	3.42	3.61	3.82	4.04	4.29	4.40
35.0	3.12	3.19	3.28	3.40	3.53	3.69	3.87	4.07	4.29	4.53	4.63
40.0	3.55	3.60	3.67	3.77	3.89	4.03	4.19	4.38	4.59	4.82	4.92
45.0	4.09	4.11	4.16	4.23	4.33	4.45	4.59	4.76	4.96	5.18	5.27
50.0	4.76	4.75	4.76	4.81	4.88	4.97	5.09	5.24	5.42	5.62	5.71
55.0	5.56	5.51	5.49	5.51	5.54	5.61	5.71	5.83	5.98	6.16	6.24
60.0						6.38	6.44	6.53	6.65	6.81	6.87

Cond °C	Current at 400 V, A										
	-40.0	-35.0	-30.0	-25.0	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0
10.0	5.82	5.89	5.98	6.10	6.25	6.42					
15.0	5.80	5.89	6.00	6.15	6.32	6.53	6.75				
20.0	5.81	5.92	6.05	6.22	6.41	6.64	6.89	7.17			
25.0	5.86	5.98	6.13	6.32	6.53	6.78	7.05	7.35	7.68		
30.0	5.97	6.10	6.27	6.47	6.70	6.96	7.26	7.58	7.92	8.30	8.45
35.0	6.16	6.30	6.48	6.69	6.93	7.21	7.52	7.85	8.22	8.61	8.78
40.0	6.44	6.59	6.77	6.99	7.25	7.54	7.86	8.21	8.59	8.99	9.16
45.0	6.83	6.98	7.17	7.40	7.66	7.96	8.29	8.65	9.04	9.46	9.63
50.0	7.35	7.50	7.70	7.92	8.19	8.49	8.83	9.19	9.59	10.02	10.20
55.0	8.02	8.17	8.36	8.58	8.85	9.15	9.49	9.86	10.27	10.71	10.89
60.0						9.96	10.30	10.68	11.08	11.52	11.71

Cond °C	Suction Mass Flow, g/s										
	-40.0	-35.0	-30.0	-25.0	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0
10.0	25.20	31.80	39.90	49.60	61.20	75.00					
15.0	25.10	31.80	39.80	49.40	60.80	74.40	90.50				
20.0	25.00	31.70	39.70	49.20	60.40	73.90	89.70	108.50			
25.0	24.90	31.60	39.50	48.90	60.00	73.30	88.90	107.50	129.50		
30.0	24.60	31.40	39.30	48.60	59.60	72.70	88.10	106.50	128.00	153.50	165.00
35.0	24.10	31.10	39.00	48.30	59.10	72.00	87.30	105.50	127.00	152.50	163.50
40.0	23.50	30.60	38.60	47.80	58.60	71.30	86.40	104.50	125.50	151.00	162.50
45.0	22.50	29.80	37.90	47.20	57.90	70.50	85.50	103.50	124.50	150.00	161.50
50.0	21.20	28.80	37.10	46.40	57.10	69.60	84.50	102.50	123.50	149.00	161.00
55.0	19.35	27.40	35.90	45.40	56.10	68.70	83.60	101.50	123.00	149.00	161.00
60.0						67.90	82.90	101.00	123.00	149.50	162.00

COMPRESSOR MECHANICAL AND PHYSICAL DATA

Displacement @ 50 Hz, m ³ /h	17.1
Length/Width, mm	246/251
Height, mm	442
Net Weight, kg	41
Gross Weight, kg	44
Rotalock Suction, inch	1 1/4
Rotalock Discharge, inch	1
Oil Quantity, l	1.9
Oil type (original charge)	POE RL32-3MAF
Oil type (approved oils)	POE RL32-3MAF, POE MOBIL EAL Arctic 22 CC
Base mounting (hole dia), mm	190 x 190 (8.5)
Sound Pressure @ 1m (LT), dBA	67
Sound Power (LT), dBA	78
Sound Power with Sound Shell (LT), dBA	72
Sound Conditions (LT, Temperatures:	-35 / 40 / 20 °C at 50 Hz
Evap./Cond./Suction at freq./speed)	
PED Category	1
Max. Internal Free Volume, l	5.70
High Side PS gauge, bar	28.8
Low Side PS gauge, bar	21
Low Side TS Max., °C	50
Refrigerant's GWP	3922
Refrigerant's classification	A1

COMPRESSOR ELECTRICAL DATA (380-420 V / 3~ / 50 Hz)

Maximum Operating Current, A	12.5
Locked Rotor Current, A	74
Winding Resistance, ohm	2.27
Default Enclosure Class	IP 21 (IEC 34)

ACCESSORIES INCLUDED

Discharge Temperature Protection	Discharge line thermostat
Mounting Grommets	Standard

ACCESSORIES OPTIONAL

Crankcase Heater	70 W External
Current Sensing Relay	External
Liquid Injection	DTC Valve
Oil Control System	ALCO Trax-Oil OM3
Sound Attenuation	Sound Shell (10dBA)
Rotalock valves	suction and discharge

MOTOR OPTIONS

Motor Code	Power Supply	Nominal Voltage, V	Start Connection	DOL Connection	Amps Factor
TFD	380-420 V / 3~ / 50 Hz	400		Y	1.00
TF5	200-220 V / 3~ / 50 Hz	200		Y	2.09
TFD	460 V / 3~ / 60 Hz	460		Y	1.04
TF5	200-230 V / 3~ / 60 Hz	230		Y	2.09