



# Opteon™ XL20

## Refrigerant (R-454C)

### Product Information

Opteon™ XL20 (R-454C) is a lower flammability, low global warming potential (GWP), hydrofluoro-olefin (HFO) - based refrigerant for new equipment. For positive displacement, direct expansion low- and medium temperature refrigeration applications, XL20 is an alternative to legacy HFC refrigerants such as R-404A, R-507, and R-407 series fluids. Opteon™ XL20 also provides an optimal balance of sustainability, performance, and safety for many heat pump applications.

With a GWP of 148(AR4), Opteon™ XL20 meets many of the application specific regulations requiring new system designs to utilize < 150 GWP refrigerants, such as the proposal in subsection (i) of the American Innovation and Manufacturing (AIM) act or F-Gas Regulation 517/2014.

Since Opteon™ XL20 is classified as a lower flammability (ISO/ASHRAE Class 2L) refrigerant, it allows for larger charge sizes compared to flammable and higher flammability ASHRAE/ISO Class 2 and 3 refrigerants. Users should always check relevant regulations and standards to verify the allowable charge, new equipment design and safe handling requirements for the intended application.

#### Applications

- Low and medium temperature commercial and industrial refrigeration systems formerly designed for high GWP HFC and HCFC refrigerants such as R-22, R-404A, R-507, and R-407 series
- Supermarkets
  - Distributed system
  - Walk in cooler/freezer, prep rooms, etc.
- Condensing units (e.g. in food service)
- Cold Storage Refrigeration
- Self-Contained refrigeration systems (e.g. ice makers, ice cream machines, etc.)
- Residential and commercial heat pumps (air to water, brine to water, etc.)

#### Benefits

- AR4 GWP of 148 (96 % reduction versus R-404A)
- Zero ozone depletion
- Better energy efficiency ratio relative to R-404A
- Minimal equipment sizing differences relative to legacy HFC/HCFC designs
- Can be topped-off after leaks
- ASHRAE Safety classification of A2L enables higher charge sizes than ASHRAE A2 or A3 refrigerants in most applications
- Miscible with POE lubricants

#### Opteon™ XL20 properties

ASHRAE Number	R-454C
Composition Weight %	R-32/R-1234yf 21.5/78.5
Molecular Weight	90.8 g/mol
Normal Boiling Point <sup>1</sup>	-45.6 °C (-50.0 °F)
Critical Pressure	4318.9 kPa (626.4 psia)
Critical Temperature	85.7 °C (186.2 °F)
Liquid Density at 21.1 °C (70 °F)	1058.2 kg/m <sup>3</sup> (66.1 lb/ft <sup>3</sup> )
Ozone Depletion Potential (CFC-11 = 1.0)	0
AR4 (AR5) GWP (CO <sub>2</sub> = 1.0)	146 (148)
ASHRAE Safety Classification	A2L
Temperature Glide	-6 K (-10.8 R)
Lower Flammability Limit <sup>2</sup>	7.7 vol%

<sup>1</sup> Normal bubble point

<sup>2</sup> ASHRAE Standard 34 - 2022 Addendum A

## Thermodynamic Performance

The tables below summarize the thermodynamic cycle performance of R-454C relative to R-404A at standard low and medium temperature refrigeration conditions.

### \*Low Temperature Model Conditions:

**40.5 °C (105 °F) Cond, -28.8 °C (-20 °F) Evap, 16.6 K (30 R) Superheat, 5.5 K (10 R) Subcool, 75% efficiency**

Refrigerant	Relative Capacity	Relative COP	Relative Mass Flow Rate	Suction Pressure kPa (psia)	Discharge Pressure kPa (psia)	Discharge Temperature °C (°F)
R-404A	1.00	1.00	1.00	213.1 (30.9)	1846.4 (267.8)	78.4 (173.1)
R-454C	0.89	1.06	0.80	167.5 (24.3)	1612.0 (233.8)	88.9 (192.1)

\*Evap and Cond temp are in mid-point

### Medium temperature Model Conditions:

**40.5 °C (105 °F) Cond, -6.7 °C (20 °F) Evap, 16.6 K (30 R) Superheat, 5.5 K (10 R) Subcool, 75% efficiency**

Refrigerant	Relative Capacity	Relative COP	Relative Mass Flow Rate	Suction Pressure kPa (psia)	Discharge Pressure kPa (psia)	Discharge Temperature °C (°F)
R-404A	1.00	1.00	1.00	486.1 (70.5)	1846.4 (267.8)	69.3 (156.8)
R-454C	0.91	1.04	0.81	397.8 (57.7)	1612.0 (233.8)	76.8 (170.2)

\*Evap and Cond temp are in mid-point

For more information on the Opteon™ family of refrigerants or other refrigerants from Chemours, visit [opteon.com](https://opteon.com)

For refrigerant related support, contact our Tech2Tech Support Team **866-433-TECH** (8324), or email [tech2tech@chemours.com](mailto:tech2tech@chemours.com)

**For more information on the Opteon™ family of refrigerants or other refrigerants from Chemours, visit [opteon.com](https://opteon.com)**

The information set forth herein is furnished free of charge and based on technical data that Chemours believes to be reliable. It is intended for use by persons having technical skill, at their own risk. Since conditions of use are outside our control, we make no warranties, expressed or implied and assume no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe any patents or patent applications.

© 2024 The Chemours Company FC, LLC. Opteon™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC. Chemours™ and the Chemours Logo are trademarks of The Chemours Company.

C-10999(1/2024)